

From: Jeff Downs [Jeff_Downs@partech.com]
Sent: Friday, May 14, 2004 7:46 AM
To: Kerr, Stephen (JITC/FHU)
Subject: RE: Mil-Std-2500C (Draft) and Associated RFCs

Hello Stephen,

Two editorial comments:

(pg 91) IC still lists J2K as "reserved for future". Is this the intention? The remainder of the document talks about C8 and M8 values for IC as though it is in current use.

(Page 109-110) Notes regarding the repetition of BMRnBNDm and TMRnBNDm is oddly worded:

Current wording:

"The BMRnBNDm record repeats; one 4 byte record for each block, and for IMODE S, one record for each block of each band in the image"

Proposed alternative:

"The BMRnBNDm record repeats. For IMODE S, BMRnBNDm repeats one 4-byte record for each block of each band in the image ($\text{Max}(\text{NBANDS}, \text{XBANDS}) * \text{NBPR} * \text{NBPC}$). For IMODE B, P, and R, BMRnBNDm repeats one 4-byte record for each block in the image ($\text{NBPR} * \text{NBPC}$).

Similarly for TMRnBNDm.

Jeff Downs
Software Engineer
PAR Government Systems Corp.
125 Tech Park Dr.
Rochester, NY, 14623
(585) 239-6013